




ECO-REVI H07Z1-K (AS)












Flexible single core non-sheathed cables, insulated with thermoplastic compound, and low emission of smoke and corrosive gases.

Uses

Specially recommended for the internal wiring of devices placed in public attendance space

Characteristics

Insulation	 PVC T17 according to UNE-EN-50363-7
Colours	 Yellow-green, orange, red, rose, violet, turquoise, blue, black, white, grey and brown
Conductor	 Copper class 5 according to UNE-EN 60228
Packing	 1.5 200 m. laminated rolls; for the other sections, 100 m. rolls
Standard	 UNE 21002
Sections	 2.5 a 240 mm²
Temperature	 70°C
Test voltage	 2500V
Rated voltage	 450/750V

Technical data

Sección mm ²	Espesor mm	Diámetro mm	Resistencia a 20 °C	
			Ohm/km	Peso aprox. Kg/Km
1,5	0,7	3	13,3	19
2,5	0,8	3,6	7,98	31
4	0,8	4,2	4,95	47
6	0,8	4,8	3,3	70
10	1	6,25	1,91	120
16	1	7,3	1,21	190
25	1,2	9,1	0,78	297
35	1,2	10,3	0,554	400
50	1,4	12,65	0,386	560
70	1,4	14,1	0,272	785
95	1,6	16,4	0,206	1025
120	1,6	18,75	0,161	1150