



Electric wire Wire 300/500 V - 450/750 V halogen free

**ECO-REVI H07Z1-K (AS)**

revi@grupo-revi.com

+34 988 215 454

grupo-revi.com



**Flexible single core non-sheathed cables, insulated with thermoplastic compound, and low emission of smoke and corrosive gases.**

## Uses

Specially recommended for the internal wiring of devices placed in public attendance space

## Characteristics

Insulation	<b>A</b>	<b>PVC T17 according to UNE-EN-50363-7</b>	Sections	<b>+</b>	<b>2.5 a 240 mm<sup>2</sup></b>
Colours	<b>🔥</b>	<b>Yellow-green, orange, red, rose, violet, turquoise, blue, black, white, grey and brown</b>	Temperature	<b>🌡️</b>	<b>70°C</b>
Conductor	<b>C</b>	<b>Copper class 5 according to UNE-EN 60228</b>	Test voltage	<b>⚡</b>	<b>2500V</b>
Packing	<b>📦</b>	<b>1.5 200 m. laminated rolls; for the other sections, 100 m. rolls</b>	Rated voltage	<b>⚡</b>	<b>450/750V</b>
Standard	<b>📄</b>	<b>UNE 21002</b>			

## Technical data

Sección mm <sup>2</sup>	Espesor mm	Diámetro mm	Resistencia a 20 °C Ohm/km	Peso aprox. Kg/Km
1.5	0.7	3	13.3	19
2.5	0.8	3.6	7.98	31
4	0.8	4.2	4.95	47
6	0.8	4.8	3.3	70
10	1	6.25	1.91	120
16	1	7.3	1.21	190
25	1.2	9.1	0.78	297
35	1.2	10.3	0.554	400
50	1.4	12.65	0.386	560
70	1.4	14.1	0.272	785
95	1.6	16.4	0.206	1025
120	1.6	18.75	0.161	1150