



Electric wire Wire 300/500 V - 450/750 V halogen free [revi@grupo-revi.com](mailto:revi@grupo-revi.com)

+34 988 215 454

[grupo-revi.com](http://grupo-revi.com)

## ECOREVI ES05Z1-K (AS)












Flexible single core non-sheathed cables, insulated with thermoplastic compound, and low emission of smoke and corrosive gases.

### Uses

For protected, fixed wiring inside devices when a low emission of smoke and corrosive gas

### Characteristics

Insulation	 <b>PVC T17 according to UNE-EN-50363-7</b>
Colours	 <b>Yellow-green, orange, red, rose, violet, turquoise, blue, black, white, grey and brown</b>
Conductor	 <b>Copper class 5 according to UNE-EN 60228</b>
Packing	 <b>200 m. laminated rolls</b>
Standard	 <b>UNE 21002</b>
Sections	 <b>0.5, 0.75 y 1 mm<sup>2</sup></b>
Temperature	 <b>70°C</b>
Test voltage	 <b>2000V</b>
Rated voltage	 <b>300/500V</b>

### Technical data

Sección mm <sup>2</sup>	Espesor mm	Diámetro mm	Resistencia a 20 °C	Peso aprox.
			Ohm/km	Kg/Km
0,5	0,6	2,6	39	9
0,75	0,6	2,8	26	12
1	0,6	3	19,5	14