




Electric wire Mangueras 300/500 V

**H05VV-F**

revi@grupo-revi.com

+34 988 215 454

grupo-revi.com













**PVC insulated and PVC sheathed flexible multipolar cables.**

## Uses

Installation in household rooms, kitchens and offices. For domestic devices, even those placed in humid spots. To be used under mean mechanical stress (for exam

## Characteristics

Insulation	 <b>PVC T17 according to UNE-21031</b>	Standard	 <b>UNE 21031</b>
Colours	 <b>White, grey or black</b>	Sections	 <b>2, 3, 4, 5 x 0.75 a 4 mm<sup>2</sup></b>
Conductor	 <b>Copper class 5 according to UNE-EN 60228</b>	Temperature	 <b>70°C</b>
Packing	 <b>100 m. laminated rolls</b>	Test voltage	 <b>2000V</b>
Single pole identification	 <b>By situation according to UNE 21089-1</b>	Rated voltage	 <b>300/500V</b>

## Technical data

Sección mm <sup>2</sup>	Espesor aislamiento mm	Espesor cubierta mm	Diámetro mm	Resistencia a 20 °C Ohm/Km
2x0,75	0.6	0.8	6.3	26
2x1	0.6	0.8	6.65	19.5
2x1,5	0.7	0.8	7.6	13.3
2x2,5	0.8	1	9.3	7.98
2x4	0.8	1.1	10.5	4.95
3G0,75	0.6	0.8	6.65	26
3G1	0.6	0.8	7.1	19.5
3G1,5	0.7	0.9	8.2	13.3
3G2,5	0.8	1.1	10.5	7.98
3G4	0.8	1.2	11.05	4.95
4G0,75	0.6	0.8	7.6	26
4G1	0.6	0.9	7.95	19.5
4G1,5	0.7	1	9.25	13.3
4G2,5	0.8	1.1	11.05	7.98
4G4	0.8	1.2	12.75	4.95
5G0,75	0.6	0.9	8	26
5G1	0.6	0.9	9	19.5
5G1,5	0.7	1.1	11.05	13.3
5G2,5	0.8	1.2	13.2	7.98
5G4	0.8	1.4	15.4	4.95